



**The ArmourFlash LoLine range of high quality, external electronic sounders provides the solution for prestigious locations where high security and robust construction are a prerequisite.**

Available in vertical and horizontal formats it is ideal for both domestic and commercial applications

Low Profile 120 dB Sounder complete with Integral Strobe

"Zinc Armoured" Housing in both horizontal and vertical formats

Stainless Steel or "Zintec" powder coated covers

Cut-off timer with 5 second engineer test facility

Comfort L.E.D.

Non Louvre design with front and back Tamper





## SPECIFICATIONS

<b>Sounder</b>	120 dB (A) @ 1 metre Sweep frequency 1.5KHz - 5.5 KHz
<b>Strobe</b>	Independent xenon strobe circuit 1 flash per second
<b>Supply Voltage</b>	11 to 14 volts DC
<b>Current consumption</b>	Sounder 300 mA / Strobe 115 mA
<b>Battery</b>	SAB 8.4V Ni-Cd 280 mAh
<b>Indication</b>	Comfort L.E.D
<b>Timer</b>	20 minute cut-off timer (5 Secs Engineer test mode)
<b>Tamper</b>	Back and screw tamper, negative or positive (universal)
<b>Conformal coating</b>	Mil-1-46058C
<b>Backplate</b>	1.2mm "Galvipan" steel
<b>Cover</b>	1mm Stainless Steel or 1.2mm UV resistant polyester powder coated "Zintec". Choice of white, red or yellow.
<b>Lens option</b>	Polycarbonate available in clear, amber, red and blue.
<b>Dimensions</b>	300 x 202 x 50 mm
<b>Printing</b>	Silk screen printing to order



**Western Technology Limited**

A Graham Whitehead Group Company

3 Farriers Way, Netherton, Bootle L30 4XL

Tel + 44 (0) 151 524 3224 Fax + 44 (0) 151 524 9435

email [sales@westech.co.uk](mailto:sales@westech.co.uk) web [www.westech.co.uk](http://www.westech.co.uk)





**ArmourPlas provides a backplate and inner shroud constructed in zinc coated steel that protects the functional components of the sounder/S.A.B. assembly. Designed for use with CQR "INTEGRA" polycarbonate bell cover, ArmourPlas is the perfect partner.**

Tamper protection is offered on the outer cover, the inner shroud, and the backplate to the wall

The strobe is mounted on the inner shroud which is aligned with the lens of the INTEGRA cover

Low Profile 120 dB sounder complete with Integral Strobe

Cut -off timer with 5 seconds engineer test facility

Non-louvre design with front and back Tamper



## SPECIFICATIONS

<b>Sounder</b>	120 dB (A) @ 1 metre Sweep frequency 1.5KHz - 5.5 KHz
<b>Strobe</b>	Independent xenon strobe 1 flash per second
<b>Supply Voltage</b>	11 to 14 volts DC
<b>Current consumption</b>	Sounder 300 mA / Strobe 115 mA
<b>Battery</b>	8.4V Ni-Cd 280 mAh
<b>Timer</b>	20 minute cut-off timer (5 Secs Engineer test mode)
<b>Tamper</b>	Universal back and screw tamper negative or positive
<b>Conformal coating</b>	Mil-1-46058C
<b>Backplate</b>	1.2 mm Zinc coated steel
<b>Shroud</b>	1.2 mm Zinc coated steel
<b>Lens</b>	Clear polycarbonate
<b>Dimensions</b>	385 x 250 x 89 mm nominal



## Western Technology Limited

A Graham Whitehead Group Company

3 Farriers Way, Netherton, Bootle L30 4XL

Tel + 44 (0) 151 524 3224 Fax + 44 (0) 151 524 9435

email [sales@westech.co.uk](mailto:sales@westech.co.uk) web [www.westech.co.uk](http://www.westech.co.uk)



Westech and ArmourPlas logos are trade marks of Western Technology Limited

Due to continuous product development Western Technology Limited reserve the right to alter specifications as and when required.